



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: PENN, Laurence Richard

SERIAL NO.: 10/642,496

FILED: August 18, 2003

TITLE: METERING DEVICE

TRANSMITTAL OF CERTIFIED COPY OF FOREIGN PRIORITY DOCUMENT

Commissioner for Patents  
P. O. Box 1450  
Alexandria, VA 22313-1450


Sir:

Attached please find the Foreign Priority Document, United Kingdom Patent Application No. 0314322.9 filed on 19 June 2003.

Respectfully submitted,

Date

9.9.03

  
\_\_\_\_\_  
John S. Egbert  
Reg. No. 30,627  
Harrison & Egbert  
412 Main Street, 7<sup>th</sup> Floor  
Houston, Texas 77002  
(713)224-8080  
(713)223-4873 (Fax)

CERTIFICATE OF MAILING UNDER 37 CFR 1.8(a)

I hereby certify that the attached CERTIFIED COPY OF FOREIGN PRIORITY DOCUMENT is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to:

Commissioner for Patents  
P. O. Box 1450  
Alexandria, VA 22313-1450

on 9.9, 2003.

Date

9.9.03

  
\_\_\_\_\_  
John S. Egbert





INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 25 July 2003





20JUN03 1316460-1 D00389  
P01/7700 0.00-0314322 6  
**1/77**

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

P16452GB - NHF/ns

2. Patent application number

(The Patent Office will fill in this part)

**0314322.9**

**19 JUN 2003**

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

Laurence Richard Penn  
14 Main Street  
Middleton  
Market Harborough  
LE16 8YU

Patents ADP number (*if you know it*)

**5771118002**

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

**IMPROVEMENTS IN OR RELATING TO A METERING DEVICE**

5. Name of your agent (*if you have one*)

Forrester Ketley & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

Forrester House  
52 Bounds Green Road  
London  
N11 2EY

Patents ADP number (*if you know it*)

**133001**

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number  
(*if you know it*)

Date of filing  
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

No, applicant is sole inventor

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

9 ✓

Claim(s)

2 ✓

Abstract

1 ✓ *mm*

Drawing(s)

2 + 2 ✓

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

X ✓

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11.

~~1~~ We request the grant of a patent on the basis of this application.

*Forrester Ketley & Co.*  
Signature

Date  
18 June 2003

Forrester Ketley & Co.

12. Name and daytime telephone number of person to contact in the United Kingdom

FRANKLAND, Nigel H.  
(020) 8889 6622

### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

### Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

**DUPLICATE**

**PATENTS ACT 1977**

P16452GB/NHF/ns

5

**DESCRIPTION OF INVENTION**

10

15

**"IMPROVEMENTS IN OR RELATING TO A METERING DEVICE"**

20

25

30

**THIS INVENTION RELATES** to a metering device and more particularly relates to a metering device of the type incorporating an elongate chamber having a shuttle contained within the chamber, the shuttle having a portion which is a substantially sealing sliding fit within the chamber, the shuttle being movable between an initial position and a second position with the chamber, each end of the chamber having a fluid flow duct through which pressurised fluid may enter and leave the chamber, there being a valve arrangement adapted to control the flow of pressurised fluid to and from the chamber such that, during successive cycles of operation of the metering device, fluid is supplied to one end of the chamber causing the shuttle to move from the initial position at the said one end of the chamber to the second position at the other end of the chamber to eject a predetermined metered volume of fluid from the chamber and subsequently fluid is supplied to the said other end of the chamber causing the shuttle to move back from the second position to the initial position again ejecting a predetermined metered volume of fluid from the chamber.

Various metering devices of this type have been proposed before and reference may be made to a WO90/10190A and WO/0075611A which disclose arrangements of this general type.

5           The GB-A-2377425 discloses a metering device of the type described above in which the valving arrangement comprises a spool valve having a spool sealingly slideable within a bore. A reciprocating mechanism is provided to drive the spool axially between two alternate positions in response to the shuttle reaching the initial position or the second position within the chamber. In one  
10 position the spool valve creates a fluid flow path for pressured liquid from a fluid flow inlet duct to one end of the chamber and also creates a fluid flow path from the other end of the chamber to a fluid flow outlet duct. In the second position of the spool a fluid flow path is created from a fluid flow inlet duct to the other end of the chamber and from the said one end of the chamber  
15 to the fluid flow outlet duct.

With a reciprocating movement the spool valve is subjected to many changes of momentum, which can cause wear in the drive mechanism.

20           The present invention seeks to provide an improved metering device.

According to this invention there is provided a metering device, the metering device incorporating an elongate chamber, there being a shuttle contained within the chamber, the shuttle having a portion which is a  
25 substantially sealing sliding fit within the chamber, the shuttle being moveable axially between an initial position and a second position within the chamber, each end of the chamber being provided with a fluid flow duct through which pressured fluid may enter and leave the chamber, there being valve arrangement to control the flow of fluid to and from the chamber such that, during

successive cycles of operation of the metering device, fluid is supplied to one end of the chamber causing the shuttle to move from the initial position at said one end of the chamber to the second position at the other end of the chamber, thus ejecting a pre-determined volume of fluid from the other end of the chamber, and subsequently fluid is supplied to said other end of the chamber causing the shuttle to move back from the second position to the initial position, ejecting a pre-determined quantity of fluid from the said one end of the chamber, the valving means comprising a rotary valve rod contained within a valve bore, and a mechanism to rotate the valve rod, the fluid flow ducts from the chamber extending to the valve bore, at least one fluid inlet extending to the valve bore and at least one fluid outlet extending from the valve bore, the valve rod, in combination with the valve bore, defining fluid flow passages which, in one orientation of the valve rod serve to interconnect a fluid flow inlet and the fluid flow duct extending to one end of the chamber whilst interconnecting the fluid flow duct extending to the other end of the chamber with an outlet and, in an alternate orientation, serving to interconnect the fluid flow inlet with the fluid flow duct extending to the other end of the bore whilst connecting the fluid flow duct extending to the said one end of the bore with an outlet.

Preferably the valve rod is rotated by a motor arrangement, the motor arrangement being controlled in response to a signal generated in response to the shuttle reaching the initial position or the second position.

Conveniently the motor arrangement is a stepping motor.

Advantageously the shuttle is provided with two rods, each rod extending beyond the chamber, there being a contact or proximity sensor located adjacent the end of each rod, to generate a said signal when the shuttle reaches the initial position and the second position.

Preferably adjustable collars are provided on the shuttle rods to limit the movement of the shuttle.

5            Conveniently at least one air bleed is provided communicating with part of said chamber to bleed air from the chamber.

In order that the invention may be more readily understood, and so that further features thereof may be appreciated, the invention will now be  
10 described, by way of example, with reference to the accompanying drawings in which:

FIGURE 1 is a partly cut-away view of a metering device in accordance with the invention;

15

FIGURE 2 is a view of the rotary valve rod;

FIGURE 3 is a diagrammatic sectional view illustrating one phase of operation of the device, and

20

FIGURE 4 is a view corresponding to Figure 3 illustrating another phase in the operation of the device.

Referring initially to Figure 1 of the accompanying drawings a metering  
25 device in accordance with the invention comprises a housing 1 which defines a cylindrical chamber 2. Contained within the chamber 2 is a shuttle 3. The shuttle 3 is a unit or assembly which has a cylindrical central cylindrical portion 4 which is a sliding sealing fit with the chamber 2. The shuttle incorporates two rods 5,6 which extend axially from opposite sides of the cylindrical portion

4 and which pass, as a sliding sealing fit through apertures formed in the end walls of the chamber 2, the rods 5,6 thus projecting beyond the housing. Mounted on the projecting portions of the rods 5,6 are adjustable collars 7,8, the position of which may be adjusted to alter the "stroke" of the metering device as will become clear from the following description. Located adjacent the ends of the rods 5,6 are sensors 9,10 which are responsive to the rods 5,6 each reaching a pre-determined position. The sensors may, ideally, be responsive to physical contact of the end of the rod with the sensor.

10 The central cylindrical portion 4 of the shuttle effectively divides the chamber 2 into two separate parts, one at the left-hand end of the chamber and the other at the right-hand end of the chamber. Respective fluid flow ducts 11,12 connect these end parts of the chamber 2 to spaced-apart points of a cylindrical valve bore 13 defined within the housing 1. Outlet and inlet ducting also communicate with the bore 13. Thus the housing defines a first outlet duct 15 offset from the duct 11 and second outlet duct 15 offset from the duct 12. The ducts 14 and 15 are off-set axially from the ducts 11 and 12, being closer to the ends of the valve bore 13, but one diametrically opposed to the ducts 11,12. A fluid inlet duct 16 is also defined located at a position between the two fluid flow ducts 11,12. Contained within the valve bore 13 is a rotary valve rod 17 which is driven rotationally by a stepping motor M in response to signals from the sensors 9,10.

25 The valve rod 17 has parts thereof cut away in the form of a channel or recess in the periphery of the rod and passages or bores through the rod so that the valve rod 17, when in the bore 13, may define fluid flow paths. The valve rod 17 is provided with a first through bore 18 which is inclined to the axis of the valve rod 17 and which, in one rotational position of the valve rod 17, when the valve rod 17 is present in the bore, serves to interconnect the fluid flow duct

11 and the outlet duct 14. A second corresponding bore 19 is provided, which is actually parallel with the first bore 18, which, as will be understood from Figure 2, in an alternate rotational position of the valve rod 17 serves to interconnect the fluid flow duct 12 and the outlet 15. Between the two bores 18,19 there is an annular groove 20 formed in the exterior surface of the valve rod 17 which is in alignment with the inlet 16. The groove 20 is provided with two diametrically opposed axial extensions 21,22, which extend in opposite axial directions. It is to be appreciated that in one rotational position of the valve rod 17 the axial extension 21 will extend to the end of the flow passage 12 thus forming a flow path from the inlet 16 to the right-hand end of the chamber 2, and in an alternate position of the valve rod 17 groove 22 will establish communication with the flow path 11.

Looking now at Figure 3 the shuttle 3 is shown, in a right-hand most position with the end of the projecting shuttle rod 6 engaging the sensor 10. As the shuttle rod 6 contacts the sensor 10, so the stepping motor M rotates the valve rod 17 by  $180^\circ$ , thus moving the valve rod 17 to the position as shown in Figure 4. When the valve rod 17 is in the orientation or the position as shown in Figure 4 the groove 20 and the axial extension 21 serve to connect the inlet 16 to the fluid flow passage 12 which communicates with the right-hand end of the chamber 2, whereas the bore 18 serves to interconnect the fluid flow duct 11 (which, in turn, communicates with the left-hand end of the chamber 2), and the outlet 14. Pressured fluid may thus flow from the inlet 16 through the annular groove 20 and the axial extension 21, through the fluid flow duct 12 into the right-hand end of the chamber 2 thus serving to move the shuttle 3 towards the left. As the shuttle 3 moves towards the left, so fluid in the right-hand end of the chamber is discharged through the fluid flow duct 11, and the bore 18 and through the outlet 14. The shuttle 3 thus continues to move towards the left until the shuttle rod 5 contacts sensor 9. When the sensor 9 is contacted, the

shuttle 3 has completed its stroke and a pre-determined quantity of fluid in the form of a metered "shot" of fluid has been ejected through the outlet 14.

In response to a signal generated by the sensor 9 when touched by the shuttle rod 5, the stepping motor M again rotates the valve rod 17 by 180°, thus returning the valve rod 17 to the position or orientation shown in Figure 3. With the valve rod 17 in the position shown in Figure 3 fluid will flow from the inlet through the annular groove 20, the axial extension 22, and through the fluid flow duct 11 to the left-hand end of the chamber 2. The bore 19 in the valve rod 17 interconnects the fluid flow duct 12 and the outlet 15, allowing fluid from the right-hand end of the chamber to flow to the outlet 15. Thus the shuttle 3 will move towards the right until the shuttle rod 6 establishes a contact with the sensor 10. As the shuttle makes the movement to the right a pre-determined quantity of fluid, in the form of a metered "shot" of fluid, is ejected from the right-hand part of the chamber 6 through the outlet 15. When the shuttle rod 6 contacts the sensor 10 the motor M is actuated again. The cycle of operation may then repeat.

Since the stepping motor M only rotates the valve rod 17 on receipt of a signal from the sensor 9 or the sensor 10, should the shuttle not be able to complete its stroke, for example due to a lack of fluid, or insufficient fluid pressure, no signal will be given and the metering unit will just stop. In this way it can be ensured that for each cycle of operation the metering unit delivers an appropriate quantity of fluid, in the form of a correctly metered "shot", which can be of crucial importance if two fluids, which are components of, for example, a two-part adhesive or the like, are to be metered by two separate metering units and mixed in a precisely pre-determined ratio.

It is to be appreciated that the position of the collars 7,8 on rods 5,6 may be adjusted and the position of the sensors 9,10 may be adjusted to increase or decrease the stroke of the shuttle, thus increasing or decreasing the quantity of fluid ejected on each stroke of the shuttle.

5

As shown in Figures 3 and 4 the chamber 2 may be provided on either side of the cylindrical portion 4 of the shuttle 3, with air bleeds 23, 24. These may be opened to permit air to escape from the chamber 2, especially when the described metering device is first filled with the fluid to be metered, to ensure  
10 that all of the air is vented away, so that hydraulic integrity can be established with no compressible air remaining in the chamber 2.

In the described embodiment the valve is a rotary valve rod, which facilitates manufacture and maintenance of the valve. In use, the valve rod may  
15 rotate almost uniformly, avoiding sudden changes of momentum as maybe experienced with a reciprocating valve.

Of course, the metering device as described may be "reversed", with pressurised fluid being supplied to the "outlets" 14,15, and with the "inlet" 16  
20 actually acting as an outlet.

Whilst the invention has been described with reference to contact sensors 9,10 responsive to contact with the shuttle rods, proximity sensors which respond when the shuttle rods reach pre-determined positions may be  
25 used.

In the present Specification "comprises" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following Claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process  
5 for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

## CLAIMS:

- 5 1. A metering device, the metering device incorporating an elongate chamber, there being a shuttle contained within the chamber, the shuttle having a portion which is a substantially sealing sliding fit within the chamber, the shuttle being moveable axially between an initial position and a second position within the chamber, each end of the chamber being provided with a fluid flow  
10 duct through which pressured fluid may enter and leave the chamber, there being valve arrangement to control the flow of fluid to and from the chamber such that, during successive cycles of operation of the metering device, fluid is supplied to one end of the chamber causing the shuttle to move from the initial position at said one end of the chamber to the second position at the other end  
15 of the chamber, thus ejecting a pre-determined volume of fluid from the other end of the chamber, and subsequently fluid is supplied to said other end of the chamber causing the shuttle to move back from the second position to the initial position, ejecting a pre-determined quantity of fluid from the said one end of the chamber, the valving means comprising a rotary valve rod contained within  
20 a valve bore, and a mechanism to rotate the valve rod, the fluid flow ducts from the chamber extending to the valve bore, at least one fluid inlet extending to the valve bore and at least one fluid outlet extending from the valve bore, the valve rod, in combination with the valve bore, defining fluid flow passages which, in one orientation of the valve rod, serve to interconnect a fluid flow inlet and the  
25 fluid flow duct extending to one end of the chamber whilst interconnecting the fluid flow duct extending to the other end of the chamber with an outlet and, in an alternate orientation, serving to interconnect the fluid flow inlet with the fluid flow duct extending to the other end of the bore whilst connecting the fluid flow duct extending to the said one end of the bore with an outlet.

2. A metering device according to Claim 1 wherein the valve rod is rotated by a motor arrangement, the motor arrangement being controlled in response to a signal generated in response to the shuttle reaching the initial position or the  
5 second position.
3. A metering device according to Claim 2 wherein the motor arrangement is a stepping motor.
- 10 4. A metering device according to Claim 2 or 3 wherein the shuttle is provided with two rods, each rod extending beyond the chamber, there being a contact or proximity sensor located adjacent the end of each rod, to generate a said signal when the shuttle reaches the initial position and the second position.
- 15 5. A metering device according to Claim 4 wherein adjustable collars are provided on the shuttle rods to limit the movement of the shuttle.
6. A metering device according to any one of Claims 1 to 5 wherein at least one air bleed is provided communicating with part of said chamber to bleed air  
20 from the chamber.
7. A metering device substantially as herein described with reference to and as shown in the accompanying drawings.
- 25 8. Any novel feature or combination of features disclosed herein.

## ABSTRACT:

**“IMPROVEMENTS IN OR RELATING TO A METERING DEVICE”**

5

A metering device that includes a housing (1) defining a cylindrical chamber (2) containing a reciprocating shuttle (3). The two opposed end parts of the chamber are interconnected by fluid flow ducts (11,12) to a cylindrical valve bore (13). Contained with the valve (4) is a rotary valve rod (17) driven rotationally by a stepping motor (M). The valve rod (17) has part cut away to form channels or recesses (18,19,20,21,22). In one rotational position of the valve rod (17) a flow path is established from an inlet (16) to one end of the chamber (2) and a separate flow path is established from the other end of the chamber to an outlet (14). In an alternate orientation of the valve rod (17) a flow path is formed from the inlet (16) to the other end of the chamber (2) and the first end of the chamber is connected to an outlet (15).




FIG 1




FIG 2



